

Nice HSDIM12 Detector



HSDIM12 infrared detector with vertical curtain lens, via radio, Dual Band, to protect doors and windows.

Supervised volumetric curtain lens detector with compact dimensions for the protection of doors and windows, also outdoors (if protected) to signal movement in the narrow band in front of the sensor.

Dual protection: unique in its category, equipped with wired NC input for connection of magnetic contacts and/or detectors for shutters with differentiated alarms (volumetric/NC input).

Adjustable: possibility of adjusting coverage on two levels, up to 3 or 6 m.

Safe: operates with a 9 V battery and is **protected against opening and removal.**

Code	Description
HSDIM12	Infrared detector with curtain lens and input for second contact (NC or pulse count); single or differentiated alarm, battery supplied. White
HSDIM12CB	Infrared detector with curtain lens and input for second contact (NC or pulse count); single or differentiated alarm, battery supplied. Brown
B9V-B	Alkaline battery 9 V (GP1604A)

Technical specifications

Code	HSDIM12	HSDIM12CB
Power supply	Alkaline battery 9 V (GP1604A), supplied	
Autonomy	Approx. 2 years	
Supervision	Approx. every 40 minutes	
Display and controls	Illumination of the Led confirms each alarm	
Inhibition of redundant alarms	2 minutes with retrigger	
Radio transmission	Digital communication on Dual Band frequency (433 and 868 MHz)	
Radio range	100 m in open field free of disturbance or approx. 20 m inside buildings	
Operating temperature	-25 ÷ +55 °C	
Dimensions (LxDxH)	33x31x135 mm	
Weight	120 g	

Coverage area

